
Section 1 - Identification of Chemical Product and Company

Clorox Australia Pty Limited
36 Gow St
Padstow, NSW 2211

Phone: (02)9794 9600
Fax (02)9794 9697

ABN 19 077 194 935

Substance: Water solution of ingredients.
Trade Name: **Armor All Tyre Foam**
Product Code: 40515
Product Use: Tyre cleaning preparation.
Creation Date: **March, 2004**
Revision Date: **October, 2006**

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Not classified as hazardous according to the criteria of ASCC Australia.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

Risk Phrases: Not Hazardous - No criteria found.

Safety Phrases: Not Hazardous - No criteria found.

SUSDP Classification: None allocated.

ADG Classification: Class 2.1, (AEROSOLS)

UN Number: 1950

Emergency Overview

Physical Description & colour: Milky white liquid.

Odour: Mild odour.

Major Health Hazards: no significant risk factors have been found for this product.

Potential Health Effects

Inhalation

Short term exposure: Significant inhalation exposure is considered to be unlikely. Available data indicates that this product is not harmful. In addition product is unlikely to cause any discomfort or irritation.

Long Term exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short term exposure: Major health effect from this product is misuse of the aerosol function. If sprayed continuously on skin or in eyes, it can cause frostbite.

Long Term exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short term exposure: Exposure via eyes is considered to be unlikely. Available data shows that this product is not harmful. If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause damage through frostbite.

Long Term exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short term exposure: Significant oral exposure is considered to be unlikely. This product is unlikely to cause any irritation problems in the short or long term.

Long Term exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

ASCC: No significant ingredient is classified as carcinogenic by ASCC.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

MATERIAL SAFETY DATA SHEET

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
Polyol	68648-65-7	0-10	not set	not set
Silicone emulsion	secret	0-50	not set	not set
Propellant blend of flammable gases	no data	3-10	not set	not set
Water	7732-18-5	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Skin Contact: Irritation is unlikely. However, if irritation does occur, flush with lukewarm, gently flowing water for 5 minutes or until chemical is removed. If in doubt obtain medical advice.

Eye Contact: No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed. Obtain medical advice if irritation becomes painful or lasts more than a few minutes.

Ingestion: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: There is a slight risk of an explosion from this product if commercial quantities are involved in a fire.

Only small quantities of decomposition products are expected from this products at temperatures normally achieved in a fire. Once propellant gas has burned off, this will only occur after heating to dryness.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Propellant is flammable but product unlikely to sustain combustion. Use extinguishing media suited to burning materials. Water fog or fine spray is the preferred medium for large fires. Aim to dilute the material with large quantities of water. If practical, contain diluted material and prevent from entering drains and water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade.

Flash point: Propellant is flammable but product unlikely to sustain combustion.

Upper Flammability Limit: Not available

Lower Flammability Limit: Not available

Autoignition temperature: Does not burn.

Flammability Class: Does not burn.

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. As a minimum, wear overalls, goggles and gloves. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Take suitable precautions eg use of non-sparking equipment to avoid creating sparks or flames which may ignite the spilled material. Leaking gases may form an explosion hazard. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. Refer to product label for specific instructions. After spills, wash area preventing runoff from entering drains.

MATERIAL SAFETY DATA SHEET

If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you probably require a license to do so. If you have any doubts, we suggest you contact your licensing authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

Exposure Limits

TWA (mg/m³)

STEL (mg/m³)

Exposure limits have not been established by ASCC for any of the known significant ingredients in this product.

Ventilation: No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that vapours and mists are minimised.

Eye Protection: Eye protection such as protective glasses or goggles is recommended when this product is being used.

Skin Protection: The information at hand indicates that this product is not harmful and that normally no special skin protection is necessary. However, we suggest that you routinely avoid contact with all chemical products and that you wear suitable gloves (preferably elbow-length) when handling this product.

Protective Material Types: There is no specific recommendation for any particular protective material type.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Milky white liquid.
Odour:	Mild odour.
Boiling Point:	Approximately 100°C at 100kPa.
Freezing/Melting Point:	Approximately 0°C.
Volatiles:	Water + propellant components.
Vapour Pressure:	2.37 kPa at 20°C (water vapour pressure).
Vapour Density:	No data.
Specific Gravity:	Approx 1.0
Water Solubility:	Completely soluble in water.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water distribution:	No data
Autoignition temp:	Does not burn.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C.

Incompatibilities: No particular incompatibilities.

Fire Decomposition: Only small quantities of decomposition products are expected from this products at temperatures normally achieved in a fire. This will only occur after heating to dryness. Carbon dioxide, and if

MATERIAL SAFETY DATA SHEET

combustion is incomplete, carbon monoxide and smoke. Water. silicon compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product is unlikely to undergo polymerisation processes.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient

Risk Phrases

No ingredient mentioned in the List of Designated Hazardous Substances is present in this product at hazardous concentrations.

Section 12 - Ecological Information

This product is biodegradable. It will not accumulate in the soil or water or cause long term problems.

Section 13 - Disposal Considerations

Disposal: Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Do not puncture or incinerate cans, even when empty. Please do NOT dispose into sewers or waterways.

Section 14 - Transport Information

ADG Code: 1950, AEROSOLS

Hazchem Code: 2T

Special Provisions: SP63, SP190, SP229, SP227

Dangerous Goods Class: Class 2.1, Flammable gases.

Packaging Group: Not applicable.

Packaging Method: No packaging methods specified.

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

Section 15 - Regulatory Information

AICS: We are unable to verify the presence of all of the ingredients in this product on the public AICS database. There are several possible reasons why this may occur. If you have any reason to be concerned about this, we suggest you call us on the number below.

Section 16 - Other Information

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail
AICS	Australian Inventory of Chemical Substances
ASCC	Office of the Australian Safety and Compensation Council
CAS Number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSDP	Standard for the Uniform Scheduling of Drugs & Poisons
UN Number	United Nations Number

MATERIAL SAFETY DATA SHEET

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the ASCC document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]

Copyright © Kilford & Kilford Pty Ltd, October, 2006.

<http://www.kilford.com.au> Phone (02)9251 4532